



Function:

The **355 FNS® Plus Series D.E. Filter** is a fiberglass reinforced polypropylene of advanced chemical resistant materials for superior strength and durability. The top manifold design features the Service-Ease grid pack for convenient one-at-a-time grid servicing.

Key Features:

- Superior strength.
- Service-Ease grid pack.
- Continuous High Flow internal air relief.
- 100% factory tested.
- Top-to-bottom backwash.
- High Flow manual air relief valve.
- Tension Control™ clamp.
- Black valves and plumbing.
- 1-1/2" bottom clean out port.
- 7-1/2" centerline bulkhead fittings.



355-P Series

Vertical Grid D.E. Filter

#355-006 D.E. Filter: 48 GPM flow rate. 21-1/2" diameter x 37" high; requires service clearance height of 48"; 24 sq. ft. of filter area.

#355-007 D.E. Filter: 72 GPM flow rate. 21-1/2" diameter x 43" high; requires service clearance height of 62"; 36 sq. ft. of filter area.

#355-008 D.E. Filter: 96 GPM flow rate; 21-1/2" diameter x 49" high; requires service clearance height of 74"; 48 sq. ft. of filter area.

#355-009 D.E. Filter: 120 GPM flow rate. 21-1/2" diameter x 55" high; requires service clearance height of 86"; 60 sq. ft. of filter area.

Model	Order #	Description	Shipping Weight
355-P-006	430-43001	Vertical Grid D.E. Filter- 48 GPM	60 lbs
355-P-007	430-43002	Vertical Grid D.E. Filter- 72 GPM	70 lbs
355-P-008	430-43003	Vertical Grid D.E. Filter- 96 GPM	80 lbs
355-P-009	430-43004	Vertical Grid D.E. Filter- 120 GPM	90 lbs